



# SureTie™

## RATCHET TIE DOWN

### OPERATING INSTRUCTIONS:

1. Place webbing around load to be secured and attach hooks to solid anchor points.
2. Place free end of webbing through slot in centre rotating spool of closed ratchet and pull webbing through. Pull to take up slack. (Refer to fig. A & B)
3. Tighten webbing by ratcheting the handle back and forth until load is well secured. There should be a minimum of two full wraps of webbing around reel when webbing is tight. (Refer to fig. C)
4. Hooks and webbing should be in line with direction of pull.
5. To lock ratchet, always leave handle in closed position. (Refer to fig. D)
6. To release, pull back unlock tab and fully open handle 180 degrees. (Refer to fig. E)
7. After the handle is completely open pull webbing out of the ratchet. (Refer to fig. F)

### SELECTION GUIDE

The following table is provided to assist you in choosing the most appropriate SureTie™ for your intended use. Careful consideration must be made to ensure your intended use does not exceed the lashing capacity stated on this pack. All Zenith SureTie™ products conform to Australian Standard AS/NZS 4380. Please refer to WARNING information inside pack before use.

	<b>100KG LIGHT DUTY</b> Surf Board, Kayak, Luggage, Push Bike, Ladder, Wheel Barrow, Boxes
	<b>200KG MEDIUM DUTY</b> Surf Board, Luggage, Push Bike, Ladder, Wheel Barrow, Boxes, Lawn Mower
	<b>430KG HEAVY DUTY</b> Motor Bike/Trail Bike, Lawn Mower, Furniture, Jet Ski, Fridge, Generator
	<b>800KG SUPER HEAVY DUTY</b> Motor Bike/Trail Bike, Ride-on Mower, Furniture, Jet Ski, Fridge, Pallets
	<b>1800KG LIGHT TRUCK</b> Pallets, Heavy Machinery, Motor Vehicle, Tractor

**Lashing Capacity** is the maximum load weight recommended for this system. Overloading may result in failure.

The 'Lashing Capacity Integrity System' is a patented innovation to help you identify the lashing capacity of your SureTie™. The system matches the colour of the webbing and contrasting coloured stitching to the lashing capacity, expressed in kilograms. Each colour and the number of lines of stitching represent a lashing capacity.

- Soft rubber grip handles
- Strong double J hooks
- Heavy duty webbing

