



FINISH CARE & MAINTENANCE

General Care and Maintenance

CLEANING.

Chemical cleaners should never be used on lane products. Cleaning should be done with a mild liquid detergent in warm water. Always rinse surfaces thoroughly with fresh water to ensure no detergent residue is left. Make sure that no fluid enters the lock cylinder.

LUBRICATING.

Key cylinders should be lubricated at least once a year. Powdered graphite is the only lubricant that Lane recommends. Oils, liquid lubricants and aerosol type lubricants should never be used.

To lubricate put a small amount on the key blade and insert the key into the lock barrel.

Turn the key a few times and move the key in and out of the lock to complete the process.

WITH REGULAR CARE AND MAINTAINENCE YOUR LANE LOCKS SHOULD LAST FOR MANY YEARS.

Caring for Stainless Steel

Stainless steel when maintained properly will retain its finish and structural integrity in a wide range of environments. Tea staining of the surface may occur. Tea staining is discoloration of the surface of stainless steel by corrosion. It is cosmetic and does not affect the structural integrity or the lifetime of the product.

Stainless steel is best cleaned using a mild detergent and a soft cloth. After washing, rinse the surface clean with cold water and wipe the surface dry with a soft cloth. During cleaning you must ensure that no water enters the lock.