
64mm HAMPTON CUP PULLS

64mm Fixing Centres | 84mm Overall Length Screws included



FITTING INSTRUCTIONS:

- 1. Using a pencil and the mounting template, mark the position of the holes. Ensure the holes are straight with the edge of the door or drawer prior to drilling.
- 2. Using a power drill and a 4.5mm drill bit, drill the holes through the door or drawer from the front face in the marked locations. To prevent damage to the back face of the door or drawer apply masking tape in the hole locations prior to drilling.
- 3. Determine the correct length of the Snap-off fixing screws, it may be necessary to snap to the correct length using a pair of pliers.
- 4. Place screw through back face of door or drawer, align with handle hole centres and fix using the screws provided with a No.2 Phillips head screwdriver.

Note: Snap-off fixing screws provided are M4x50mm which are designed with 5 break points at 20,26,32,38 & 44mm. The break points allow the length of the screw to be adjusted to suit the thickness of the material the handle is being fixed too.

TOOLS REQUIRED:

Drill, pencil, 4.5mm drill bit, No.2 Phillips head screwdriver, pliers.

CARE & MAINTENANCE:

For longer lasting knobs and handles, clean with warm soapy water and dry with a dean cloth. Avoid the use of household cleaners that may have harmful chemicals that can strip the protective layers, and never use abrasive scouring pads which can damage an scratch the surface of the knob or handle.

COMPLIMENTARY KNOBS AVAILABLE









Made in China Distributed by ITW Proline sion of ITW Australia Pty Ltd Newton Road, Wetherill Park NSW 2164 Australia. T 1300 721 738 www./twproVne.com.au ITW Proline — A Division of ITW New Zealand Ltd. 8 Orbit Drive, Albany, Auckland 0632 New Zealand

www.lha.co.az ABN 63 004 235 063 ight 2016, © Trademark of ITW Australia Ply Ltd



Mounting Template 64mm



