

Product Disclosure Information Sheet Landscape Construction screw

Product description

Landscape Construction screw 18g

Relevant building code clauses

B1 Structure — B1.3.1, B1.3.2, B1.3.3 (b, d, e, f, g, h, i, j, p, q), B1.3.4

B2 Durability — B2.3.1 (a)

Primary Use

Timber fastening

Scope of use

Buildex fasteners are intended for use in residential and commercial timber construction to secure various building components to timber.

For framing, use in "Framing in 'closed areas' including roof spaces" according to Table 4.3 NZS 3604

Conditions of use

Joints need to be designed so that they comply with the load requirements of B1 without exceeding the fastener capacity.

Fasteners need to be installed by a competent professional in accordance with the manufacturer's recommendations.

Installation Instructions:

1. Choose a screw long enough to allow adequate embedment into the wood being fastened to.
2. Fit screw to an impact driver and set to High. Place screw at fastening position.
3. Push sharply on impact driver to create a starting point.
4. Squeeze impact driver trigger and maintain firm end pressure until the screw has drilled and fastened.

Pre-drilling a 5mm hole is recommended in hardwood.

For optimum performance, use a Buildex T40 Star Drive Bit.

Manufacturing Details

Screws manufactured in Taiwan to strict ITW Buildex design and specifications

Warnings and bans

At the time of print, this product is not subject to any known warnings and bans found in Building Act 2004.



Product List					
Landscape Construction screw					
Climacoat					
Material	Thickness	TPI (Threads Per Inch)	Length	Quantity	Product Code
Carbon Steel	18g	7	150mm	25	X897328
			200mm		X897335
			250mm		X897342
			300mm		X897359

