

## Product Disclosure Information Sheet Tek's Hex head screw with seal

### Product description

Tek's Hex head screw with seal M6

### Relevant building code clauses

B1 Structure — B1.3.1, B1.3.2, B1.3.3 (b, d, e, f, g, h, i, j, p, q), B1.3.4

B2 Durability — B2.3.1 (a)

### Primary Use

Fastening to metal

### Scope of use

Buildex fasteners are intended for use in residential and commercial timber construction to fasten building components to metal.

For framing, use in "Framing in 'closed areas' including roof spaces" according to Table 4.3 NZS 3604.

Exterior Use

Prior to fastening a 7mm clearance hole in the timber section is recommended

### Conditions of use

Joints need to be designed so that they comply with the load requirements of B1 without exceeding the fastener capacity.

Fasteners need to be installed by a competent professional in accordance with the manufacturer's recommendations.

### Installation Instructions:

1. Use a 5/16" Hex Socket.
2. Use a mains powered or cordless screw driver with a drive speed of 3,000 RPM maximum.
3. Fit the driver bit into the screw and place at the fastening position.
4. Apply consistently firm pressure (end load) to the screw driver until the screw has fastened

### Manufacturing Details

Screws manufactured in Taiwan to strict ITW Buildex design and specifications

### Warnings and bans

At the time of print, this product is not subject to any known warnings and bans found in Building Act 2004.



Product List					
Teks Hex head screw with seal					
Climaseal 3					
Material	Thickness	TPI (Threads Per Inch)	Length	Quantity	Product Code
Carbon Steel	12g	14	20mm	50	X727478
				100	X035009
				500	X082461
			35mm	50	X702826
				100	X035146
				250	X933330
			50mm	50	X703878
				100	X035177
				250	X933347
			65mm	50	X085837

