

Product Disclosure Information Sheet Treated pine screw (RapidDrive with Star Drive)

Product description

Treated pine screw (RapidDrive with Star Drive) M6

Relevant building code clauses

B1 Structure — B1.3.1, B1.3.2, B1.3.3 (b, d, e, f, g, h, i, j, p, q), B1.3.4

B2 Durability — B2.3.1 (a)

Primary Use

Timber fastening

Scope of use

Buildex fasteners are intended for use in residential and commercial timber construction to secure building components to timber.

For framing, use in "Framing in 'closed areas' including roof spaces" according to Table 4.3 NZS 3604

Conditions of use

Joints need to be designed so that they comply with the load requirements of B1 without exceeding the fastener capacity.

Fasteners need to be installed by a competent professional in accordance with the manufacturer's recommendations.

Installation Instructions:

1. Choose a screw long enough to allow adequate embedment into the timber being fastened to.
2. Fit driver bit into impact /drill driver and set to High.
3. Insert screw head into driver bit and place screw tip at fastening position on substrate.
4. Squeeze impact / drill driver trigger and maintain firm pressure until the screw has fastened.

Not recommended for decking, please use specific Buildex decking screws.

Manufacturing Details

Screws manufactured in Taiwan to strict ITW Buildex design and specifications

Warnings and bans

At the time of print, this product is not subject to any known warnings and bans found in Building Act 2004.



Product List					
Treated pine screw (RapidDrive with Star Drive)					
Climacoat					
Material	Thickness	TPI (Threads Per Inch)	Length	Quantity	Product Code
Carbon Steel	10g	10	50mm	50	X526464
				500	X526488
			65mm	50	X526495
				500	X526501
			75mm	50	X526518
				500	X526532
	100mm	50	X526556		
		500	X526570		
	12g	8	50mm	50	X528086
				500	X528093
			75mm	50	X528109
				500	X528116
			100mm	50	X528154
				50	X528208
	125mm	250	X528253		

