

## Product Disclosure Information Sheet Bugle Batten TEKS screw

### Product description

Bugle Batten TEKS screw 14g

### Relevant building code clauses

B1 Structure — B1.3.1, B1.3.2, B1.3.3 (b, d, e, f, g, h, i, j, p, q), B1.3.4

B2 Durability — B2.3.1 (a)

### Primary Use

Timber fastening

### Scope of use

Buildex fasteners are intended for use in residential and commercial construction to secure various building components to metal.

For framing, use in "Framing in 'closed areas' including roof spaces" according to Table 4.3 NZS 3604.

Prior to fastening a 7mm clearance hole in the timber section is recommended

Max. 3mm metal drill capacity

### Conditions of use

Joints need to be designed so that they comply with the load requirements of B1 without exceeding the fastener capacity.

Fasteners need to be installed by a competent professional in accordance with the manufacturer's recommendations.

### Installation Instructions:

1. Use a 5mm Internal Hex Drive Bit.
2. Use a mains powered or cordless screw driver with a drive speed of 3,000 RPM maximum.
3. Fit the driver bit into the screw and place at the fastening position.
4. Apply consistently firm pressure (end load) to the screw driver until the screw has fastened.

Max. 3mm metal drill capacity

### Manufacturing Details

Screws manufactured in Taiwan to strict ITW Buildex design and specifications

### Warnings and bans

At the time of print, this product is not subject to any known warnings and bans found in Building Act 2004.



Product List					
Bugle Batten TEKS screw					
Zinc Alloy					
Material	Thickness	TPI (Threads Per	Length	Quantity	Product Code
Carbon Steel	14g	10	50mm	100	X511538
			75mm		X511545
			100mm		X511552
			125mm		X511569

