

Product Disclosure Information Sheet Decking screw (Star Drive)

Product description

Decking screw (Star Drive) 10g & 12g

Relevant building code clauses

B1 Structure — B1.3.1, B1.3.2, B1.3.3 (b, d, e, f, g, h, i, j, p, q), B1.3.4

B2 Durability — B2.3.1 (a)

Primary Use

Timber fastening

Scope of use

Buildex fasteners are intended for use in residential and commercial timber construction to fasten timber.

Able to be used in Corrosion zones B, C and D in sheltered and exposed areas according to Table 4.3 NZS 3604

Conditions of use

Joints need to be designed so that they comply with the load requirements of B1 without exceeding the fastener capacity.

Fasteners need to be installed by a competent professional in accordance with the manufacturer's recommendations.

Installation Instructions:

1. Choose a screw long enough to provide a minimum of 25mm thread embedment into the timber being fastened to.
2. To prevent timber splitting pre-drill a 4mm pilot hole and countersink prior to fixing.
3. Fit screw to a power screwdriver then set to Low and place at fastening position.
4. Push sharply to create a starting point.
5. Apply firm and even pressure until head is flush with surface - do not over torque.

Manufacturing Details

Screws manufactured in Taiwan to strict ITW Buildex design and specifications

Warnings and bans

At the time of print, this product is not subject to any known warnings and bans found in Building Act 2004.



Product List					
Decking screw (Star Drive)					
304 Stainless Steel					
Head Type	Thickness	TPI (Threads Per	Length	Quantity	Product Code
Star Drive (XL)	12g	11	50mm	50	X982444
				250	X982468
			65mm	50	X982451
				250	X982475

316 Stainless Steel					
Head Type	Thickness	TPI (Threads Per Inch)	Length	Quantity	Product Code
Star Drive	10g	8	50mm	50	X523814
				500	X523906
			65mm	50	X523913
				500	X528819
		9	50mm	50	X524194
				500	X524286
			65mm	50	X524316
				500	X524415

