

Product Disclosure Information Sheet Decking screw (Treated Pine)

Product description

Decking screw (Treated Pine) 10g

Relevant building code clauses

B1 Structure — B1.3.1, B1.3.2, B1.3.3 (b, d, e, f, g, h, i, j, p, q), B1.3.4

B2 Durability — B2.3.1 (a)

Primary Use

Timber fastening

Scope of use

Buildex fasteners are intended for use in residential and commercial timber construction to fasten timber.

For framing, use in "Framing in 'closed areas' including roof spaces" according to Table 4.3 NZS 3604

Conditions of use

Joints need to be designed so that they comply with the load requirements of B1 without exceeding the fastener capacity.

Fasteners need to be installed by a competent professional in accordance with the manufacturer's recommendations.

Installation Instructions:

1. Choose a screw long enough to provide a minimum of 25mm thread embedment into the timber being fastened to.
2. To prevent timber splitting pre-drill a 3.5mm pilot hole and countersink when fixing butt joints and ends. For composite decking pre-drill and countersink for all screws.
3. Fit screw to a power screwdriver then set to Low and place at fastening position.
4. Push sharply to create a starting point.
5. Apply firm and even pressure until head is flush with surface - do not over torque.

Manufacturing Details

Screws manufactured in Taiwan to strict ITW Buildex design and specifications

Warnings and bans

At the time of print, this product is not subject to any known warnings and bans found in Building Act 2004.



Product List						
Decking screw (Treated Pine)						
Climacoat						
Material	Head Type	Thickness	TPI	Length	Quantity	Product
Carbon Steel	Square Drive	10g	8	40mm	100	X940369
					250	X940406
				45mm	250	X940413
					50mm	100
				250		X940420
				500		X968967
	1000			X996267		
	65mm			100	X940390	
				250	X940437	
				500	X996274	
	Star Drive			50mm	100	X524002
					500	X524071
				65mm	100	X524064

