

Product Disclosure Information Sheet Fibre Cement screw

Product description

Fibre Cement screw 9g

Relevant building code clauses

B1 Structure — B1.3.1, B1.3.2, B1.3.3 (b, d, e, f, g, h, i, j, p, q), B1.3.4

B2 Durability — B2.3.1 (a)

Primary Use

Fastening fibre cement sheet to timber

Scope of use

Buildex fasteners are intended for use in residential and commercial timber construction to secure various building components to timber.

For framing, use in "Framing in 'closed areas' including roof spaces" according to Table 4.3 NZS 3604

Designed for fixing fibre cement sheeting (4.5-12mm) to soft timber or light gauge steel studs. Typical applications are fixing fibre cement sheets to eaves, fascias, wet areas, ceilings, interior walling and cladding.

Conditions of use

Joints need to be designed so that they comply with the load requirements of B1 without exceeding the fastener capacity.

Fasteners need to be installed by a competent professional in accordance with the manufacturer's recommendations.

Installation Instructions:

1. Use T25 Star drive bit
2. Fit screw to a power screwdriver then set to High (recommended driver speed 3,000 RPM) and place at fastening position.
3. Push sharply to create a starting point.
4. Drive screw home until head is flush or slightly below the surface.

DO NOT OVER DRIVE

Manufacturing Details

Screws manufactured in Taiwan to strict ITW Buildex design and specifications

Warnings and bans

At the time of print, this product is not subject to any known warnings and bans found in Building Act 2004.



| Product List | | | | | |
|--------------------|-----------|------------------|--------|----------|--------------|
| Fibre Cement screw | | | | | |
| Zinc Alloy | | | | | |
| Material | Thickness | TPI (Threads Per | Length | Quantity | Product Code |
| Carbon Steel | 9g | 10 | 32mm | 500 | X998261 |
| | | | | 1000 | X998254 |

